



Pool Hibernation™ Operation Instructions For Fall Closings

The 1-2 Winterizing Punch!

1. FROG Leap Depth Charge™ removes contaminants to keep water crystal clear.




2. FROG Leap ALL-OUT™ prevents algae to prepare the pool for a smoother spring start-up.

1. FROG Leap Depth Charge

Before lowering the water level and discarding the used FROG Leap Anti-Bac Mineral Pac, insert FROG Leap Depth Charge using steps 1 through 7.



1. With the circulation system off, set control dial to 0 and remove the cap to the FROG Leap or POOL FROG System.



2. Remove caps from FROG Leap Depth Charge with a pliers or other suitable tool.



3. Turn FROG Leap Depth Charge over so open ends face down and insert into the center of the FROG Leap Anti-Bac Mineral Pac. The ends of the pac will align with an L-shaped key in the system. **DO NOT FORCE.**

KING TECHNOLOGY, INC.

530 11th Avenue South • Hopkins, MN 55343
952-933-6118 • FAX 952-933-2206 • www.kingtechnology.com



4. Replace cap on FROG Leap or POOL FROG System and set dial to **Setting 5**.



6. Remove the empty FROG Leap Depth Charge and discard or recycle.



1. Turn off pump and turn dial to Setting 0 and remove cap from the FROG Leap or POOL FROG System.

2. Remove cap from FROG Leap ALL-OUT without removing seal.

NOTE: Avoid adding other chemicals until this product has been circulated (filtered) for at least 24 hours.

3. Insert upside down into center of FROG Leap Anti-Bac Mineral Pac pushing down firmly on key to puncture seal.

4. Replace cap by hand only. **DO NOT OVER TIGHTEN.** Turn control dial to **Setting 5**.




2. FROG Leap ALL-OUT

Wait 24 hours after FROG Leap Depth Charge to dispense FROG Leap ALL-OUT algae preventative following steps 1-7:



5. Turn pump on for 90 minutes allowing FROG Leap ALL-OUT to circulate through pool.



6. To remove FROG Leap ALL-OUT, turn pump off, turn dial to 0, remove system cap.



7. Lift FROG Leap ALL-OUT up and allow any water in the container to drain through the system before recycling or discarding in trash. **NOTE: If water shows more than a hint of blue inside FROG Leap or POOL FROG System, replace the cap, turn dial to Setting 5 and run the pump for one minute.**

7A. If pool size requires additional FROG Leap ALL-OUT, repeat steps 1-7.

Ensure a worry free off season as your pool sleeps away the winter months.

U.S. Patent Numbers: D410,520; 6,210,566; 6,544,415; 6,814,095; 6,948,510 and other U.S. and Foreign patents pending.

553101143N 20-48-0261



5. Turn on pump and allow 1 hour for the product to slowly dispense into the pool. If after 1 hour, the pac still contains some ingredient, re-insert, replace cap and run the circulation for an additional 30 minutes.



7. Replace cap on FROG Leap or POOL FROG System and allow circulation to run at least 15 minutes before inserting any other FROG pac products.

All components are recyclable when finished dispensing.